

CyberPower

P2WU  
WALL-TAP  
SURGE PROTECTOR

Protect home and office computers,  
and electronics.

Combining form and function, the CyberPower P2WU protects electronics, and the contemporary design helps it blend into a modern home. The two side-facing outlets give the front a clean look, while the low profile contour helps it fit into tight plug-in locations.

As a surge suppressor, it will prevent electrical spikes from reaching your appliances and small electronics. With three USB ports, the P2WU can conveniently charge three devices in one location. Plus, it's backed by a One-Year Limited Warranty and a \$50,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 500 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 2 x NEMA 5-15R
- USB charge ports: 3 (4.2-Amp)
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$50,000

SPECIFICATIONS

INPUT	
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Input Voltage	125 VAC
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	2 x NEMA 5-15R
Outlets - Total	2
USB Charge Port	Yes
USB Charge Port Amperage	4.2 Amps (Shared)
USB Charge Port Quantity	3
USB Charge Port Type	3 x Type A
USB Charge Port Voltage	5 VDC

P2WU

WALL-TAP SURGE PROTECTOR

SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING	
Clamping Voltage	800V (H-N)
EMI/RFI Filtration	No
Maximum Surge Current	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
PHYSICAL	
Color	White
Form Factors Supported	Direct plug
Material of Construction	Plastic

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	7.49 x 6.15 x 8.23 cm
Physical Dimensions - Width/Height/Depth (mm)	75 x 61 x 82 mm
Physical Dimensions - Width/Height/Depth (in.)	2.95 x 2.42 x 3.24 in.
Weight (kg)	0.16 kg
Weight (lb)	0.36 lbs.
Country of Origin	China
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	7.92 x 6.99 x 12.07 cm
Shipping Dimensions - Width/Height/Depth (mm)	79.25 x 69.85 x 120.65 mm
Shipping Dimensions - Width/Height/Depth (in)	3.12 x 2.75 x 4.75 in.
Shipping Weight (kg)	.23 kg
Shipping Weight (lbs.)	.50 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498a UL1363 UL1449 UL1310 FCC DOE VI
WARRANTY	
CEG Amount	\$50,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited